

Altos | T

T110 F3

The Altos T110 F3 delivers true server-class features and expandability along with best price-performance technology to assure the success of your business. This single-socket tower server features an 80 PLUS[®] efficient power supply that runs smoothly and quietly for maximized productivity.

Smart investment for your growing business

Driven by Intel® architecture, with great memory capacity and high performance, this tower server uses industry-leading 22 nm processors that handle large workloads more efficiently. Flexible expansion slots, plus up to 16 TB of space for data storage satisfy the demands of your growing business.

Meeting business needs with best value

The Altos T110 F3 is packed with dependable server-class hardware, including an integrated Gigabit Ethernet controller for speedy and safe data transmission, and built-in 6-channel SATA with software RAID 0, 1, 5 or 10 to ensure data security.

Fundamental management, easy use

This server provides comprehensive management utilities, including Acer Smart Setup for rapid server configuration. In addition, front-panel system health LED indicators let you check the server at a glance.

Cost-effective expandability, green computing

The Altos T110 F3 is designed with a tool-less chassis that enables easy component access, reducing maintenance and service costs. What's more, this tower server is ENERGY STAR® certified and equipped with an 80 PLUS® power supply for maximum energy efficiency.



Altos T110 F3 SPECIFICATIONS



| Mainboard | Processor type | Intel® Xeon® E3-1200 v3 processors | Intel [®] Core [™] i3 processors | | Intel® Pentium® processors | |
|-------------------------|---|---|--|---|----------------------------|--|
| | Chipset | Intel® C222 chipset | | · | | |
| | Graphics | Embedded controller: | | | | |
| | | 32 MB dedicated memory | | | | |
| | Number of processors | 1 (4 or 2 cores) | | | | |
| | Memory | 4 x DIMM slots (2 DIMMs per channel) | | | | |
| | | Up to 32 GB, using unbuffered DDR3L ECC DIMM | | | | |
| | Expansion slots | • PCle® 3.0¹ x16 (x16 connector) | | | | |
| | | PCle® 2.0 x4 (x8 connector) | | | | |
| | | PCle[®] 2.0 x1 (x8 connector) | | | | |
| | | PCle® 2.0 x1 (x4 connector) | | | | |
| | Onboard ports | Front: | | Rear | | |
| | | 2 x USB 3.0 ports | | Video port | | |
| | | | | Serial port | | |
| | | | | Gigabit LAN | | |
| | | | | • 6 x USB 2.0 p | orts | |
| | SATA RAID ² | Intel® C222 chipset with RSTe RAID support, SATA RAID 0, 1, 5, 10 default | | | | |
| | SAS RAID | SAS RAID 0, 1, 5, 10 support via optional SAS RAID add-on card | | | | |
| | Network controller | Single-port Gigabit Ethernet control | | | | |
| Security and service | | Power/reset button lockout | Administrator / user password | | Device boot control | |
| features | | Optional TPM 1.2 | Power-on password Setup password | a | BIOS write-protected | |
| Sub-system availability | Power supply | 500 W 80 PLUS® Bronze-level fixed power supply, or 500 W 80 PLUS® Gold-level fixed power supply | | | | |
| | System cooling | Active CPU heat sink | | | | |
| | | Fixed system fan | | | | |
| | Storage | Up to 4 x 3.5" SATA or up to 4 x 3.5" SAS | | | | |
| | • | Optional half-height SuperMulti optical drive | | | | |
| Chassis | Form factor | Micro ATX Tower | | | | |
| | Removable media bays | | | | | |
| | Dimensions | 180 (W) x 450 (D) x 358 (H) mm (7.1 x 17.7 x 14.1 inches) with bezel | | | | |
| | Weight | 7.9 - 12.4 kg (17.4 - 27.3 lbs.) | | | | |
| OS support | | Microsoft® Windows Server® 2012 | | Red Hat® Enterp | | |
| | | Microsoft® Windows Server® 2008 R2 SP1 | | Novell® SUSE® Linux® Enterprise Server 11 SP3 | | |
| | | Red Hat® Enterprise Linux® 6.4 | | VMware ESXi 5. | U update 1 | |
| Server management | | Acer Smart Setup | | | | |
| utilities and | | | | | | |
| applications | | | | | | |
| Warranty | 1 year onsite intervention, and 2 nd and 3 rd year free spare parts standard warranty or choose extended warranties and services ³ | | | | | |
| Regulatory compliance | Emissions classification (EMC) | CE (Class B) | BSMI (Class B) | | FCC (Class B) | |
| | Industry standard compliance / safety | CB MET | GS | ccc | Energy Star 1.1 | |

- 1. PCle® 3.0 support with Intel® Xeon® E3-1200 v3 processors and select Intel® Core™ i3 and Intel® Pentium® processors.
- 2. Integrated SATA RAID on this model supports RAID 0, 1, 5, 10 on Windows® OS only.
- 3. Extended warranty services may vary by country. Please contact your Acer authorized reseller for more information.

In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available for this model. Availability may vary depending on region. Acer disclaims any liability for errors and omissions in product descriptions.

© 2013. All rights reserved.

Acer and the Acer logo are registered trademarks of Acer Inc. Intel, Intel Core, Pentium and Xeon are trademarks of Intel Corporation in the U.S. and other countries. Other trademarks, registered trademarks and/or service marks, indicated or otherwise, are the properties of their respective owners.

About Acer

Established in 1976, Acer is an information and communication technology company dedicated to the research, design, marketing, sale and support of innovative products that enhance people's lives. Acer's green supply chain delivers environmentally friendly PCs, displays, projectors, servers, tablets and smartphones — tools our customers need to explore beyond limits and experience more. Ranked No. 3 for notebooks globally (IDC 2012), Acer employs 8,000 people, and 2012 revenues reached US\$14.7 billion. Please visit www.acer.com for more information.

